

Automatic Conveyor Tunnel Metal Detector



Brief Introduction

Tunnel Metal detector is used to detect whether metal foreign objects are mixed in products. The core part is the detection head (probe), based on the electromagnetic induction technology of the balanced coil, which can detect various metal foreign objects such as iron, aluminum, copper, stainless steel etc. Metal detector not only suitable for detecting "dry" products such as biscuits, candies, dried fruits, quick-frozen products and other non-conductive or weakly conductive products, but also suitable for detecting "wet" products such as fresh meat, seafood, fresh vegetables, sauce products, and pickled products etc., cooked food and other highly conductive products. Conveyor metal detectors are mainly composed of detection heads, conveyors and electric boxes, which are widely used in food industry, pharmaceutical industry, chemical raw materials, rubber products, paper products, ceramic products, plastic products, cigarette industry, wood processing industry, textiles, clothing, footwear, aquatic products processing industry for metal detection.

Advantages

- Good sensitivity
- Working stable, more than 20 years design and manufacture experiences
- Long life: many machines working more than 10 years
- Easy operation, no need special training
- Maintenance free







Product E-Catalogue

Features

- Digital Signal Process Technology, high stability and high sensitivity
- "Dry/Wet" products can detected on the same machine, save machine costs
- Auto Product learn ensure operator without training can use machine well
- Multiple different products parameters preset, easy to recall and edit
- Color touch screen or LCD display, multi-function operation interface
- System Password protection function to avoid parameters modified by unauthorized person
- Fast assemble and disassemble conveyor design, daily maintenance convenient
- Multiple Languages operation system including Chinese, English, Spanish, Portuguese, Polish, Czech languages for option
- Full stainless steel 304 structure meet requirement of HACCP
- Multiple rejectors for option including air jet, air pusher, flapper, belt drop-down, motor driven roller conveyor etc.

Application

- Designed for detecting all kinds of metals in food, pharmaceutical products such as quick-frozen food, dehydrated vegetables, meat, cooked food, sauce etc.
- Designed for detecting all kinds of metals in chemical, rubber, tobacco products etc.
- Designed for keeping equipments safe to avoid equipments broken by metals.
- Suitable for below different applications

1) Bakery Products metal detection









Product E-Catalogue

2) Fresh Meats and Frozen metal detection











Product E-Catalogue

5) Packing Material Metal Detection








6) Pharma products metal detection



7) Other Industrial products metal detection







Product E-Catalogue

ModelDetection WidthDetection HeightBelt WidthConveyor LengthSpeed (m/min.)Sensitivity (Without product's effect)SBI-3010260mm70mm210mm1200mm25Fe Ф0.7mm; Non-Fe Ф0.8mm; SUS304 ФSBI-3015260mm120mm210mm1200mm25FeФ0.8mm; Non-FeФ1.0mm; SUS304 ФSBI-3020260mm170mm210mm1400mm25FeФ1.0mm; Non-FeФ1.5mm; SUS304 ФSBI-3025260mm220mm210mm1500mm25FeФ1.5mm; Non-FeФ1.8mm; SUS304 ФSBI-3030260mm270mm210mm1600mm25.FeФ1.5mm; Non-FeФ2.0mm; SUS304 Ф	.5mm .0mm .5mm .0mm .2mm .5mm
Width Height Width Length (m/min.) (Without product's effect) SBI-3010 260mm 70mm 210mm 1200mm 25 Fe Φ0.7mm; Non-Fe Φ0.8mm; SUS304 Φ SBI-3015 260mm 120mm 210mm 1200mm 25 FeΦ0.8mm; Non-FeΦ1.0mm; SUS304Φ1 SBI-3020 260mm 170mm 210mm 1400mm 25 FeΦ1.0mm; Non-FeΦ1.0mm; SUS304Φ2 SBI-3025 260mm 220mm 210mm 1400mm 25 FeΦ1.5mm; Non-FeΦ1.5mm; SUS304Φ2 SBI-3025 260mm 220mm 210mm 1500mm 25 FeΦ1.5mm; Non-FeΦ1.8mm; SUS304Φ2 SBI-3030 260mm 270mm 210mm 1600mm 25. FeΦ1.5mm; Non-FeΦ2.0mm; SUS304Φ3	.5mm .0mm .5mm .0mm .2mm .5mm
SBI-3015 260mm 120mm 210mm 1200mm 25 FeΦ0.8mm; Non-FeΦ1.0mm; SUS304Φ1 SBI-3020 260mm 170mm 210mm 1400mm 25 FeΦ1.0mm; Non-FeΦ1.5mm; SUS304Φ2 SBI-3025 260mm 220mm 210mm 1500mm 25 FeΦ1.5mm; Non-FeΦ1.8mm; SUS304Φ2 SBI-3030 260mm 270mm 210mm 1600mm 25. FeΦ1.5mm; Non-FeΦ2.0mm; SUS304Φ2	.5mm .0mm .5mm .0mm .2mm .5mm
SBI-3020 260mm 170mm 210mm 1400mm 25 FeΦ1.0mm ; Non-FeΦ1.5mm; SUS304Φ2 SBI-3025 260mm 220mm 210mm 1500mm 25 FeΦ1.5mm ; Non-FeΦ1.8mm; SUS304Φ2 SBI-3030 260mm 270mm 210mm 1600mm 25. FeΦ1.5mm ; Non-FeΦ2.0mm; SUS304Φ3	.0mm .5mm .0mm .2mm .5mm
SBI-3025 260mm 220mm 210mm 1500mm 25 FeΦ1.5mm ; Non-FeΦ1.8mm; SUS304Φ2 SBI-3030 260mm 270mm 210mm 1600mm 25. FeΦ1.5mm ; Non-FeΦ2.0mm; SUS304Φ3	.5mm .0mm .2mm .5mm
SBI-3030 260mm 270mm 210mm 1600mm 25. FeΦ1.5mm ; Non-FeΦ2.0mm; SUS304Φ3	.0mm .2mm .5mm
	.2mm .5mm
	.5mm
SBI-4010 360mm 70mm 310mm 1200mm 25 FeФ0.7mm ; Non-FeФ0.8mm; SUS304Φ1	
SBI-4015 360mm 120mm 310mm 1200mm 25 FeΦ0.8mm ; Non-FeΦ1.0mm; SUS304Φ1	0
SBI-4020 360mm 170mm 310mm 1400mm 25 FeΦ1.0mm ; Non-FeΦ1.5mm; SUS304Φ2	.omm
SBI-4025 360mm 220mm 310mm 1500mm 25 FeФ1.5mm ; Non-FeФ1.8mm; SUS304Ф2	.5mm
SBI-4030 360mm 270mm 310mm 1600mm 25 FeФ2.0mm ; Non-FeФ2.38mm; SUS304Ф	3.5mm
SBI-4040 360mm 370mm 310mm 1900mm 18 FeФ2.5mm ; Non-FeФ3.0mm; SUS304Ф4	.5mm
SBI-5010 460mm 70mm 410mm 1400mm 25 FeФ0.7mm ; Non-FeΦ1.0mm; SUS304Φ1	.5mm
SBI-5015 460mm 120mm 410mm 1400mm 25 FeФ0.8mm ; Non-FeΦ1.2mm; SUS304Φ1	.5mm
SBI-5020 460mm 170mm 410mm 1400mm 25 FeΦ1.2mm ; Non-FeΦ1.8mm; SUS304Φ2	.5mm
SBI-5025 460mm 220mm 410mm 1500mm 25 FeФ1.5mm; Non-FeФ2.0mm; SUS304Ф3	.0mm
SBI-5030 460mm 270mm 410mm 1600mm 25 FeФ2.0mm ; Non-FeФ2.6mm; SUS304Ф3	.5mm
SBI-5040 460mm 370mm 410mm 1900mm 18 FeФ2.5mm ; Non-FeФ3.0mm; SUS304Ф4	.5mm
SBI-6010 560mm 70mm 510mm 1400mm 25 FeΦ0.8mm ; Non-FeΦ1.2mm; SUS304Φ1	.5mm
SBI-6015 560mm 120mm 510mm 1400mm 25 FeФ1.0mm ; Non-FeФ1.5mm; SUS304Ф2	.0mm
SBI-6020 560mm 170mm 510mm 1400mm 25 FeΦ1.5mm ; Non-FeΦ1.8 mm; SUS304Φ2	2.5mm
SBI-6025 560mm 220mm 510mm 1500mm 25 FeФ1.5mm ; Non-FeФ2.0mm; SUS304Ф3	.0mm
SBI-6030 560mm 270mm 510mm 1600mm 25 FeФ2.0mm ; Non-FeФ2.6mm; SUS304Ф3	.5mm
SBI-6040 560mm 370mm 510mm 1900mm 20 FeФ2.5mm ; Non-FeФ3.0mm; SUS304Ф3	.5mm
SBI-7010 660mm 70mm 610mm 1400mm 25 FeΦ0.8mm ; Non-FeΦ1.2mm; SUS304Φ1	.5mm
SBI-7015 660mm 120mm 610mm 1400mm 25 FeФ1.0mm ; Non-FeФ1.5mm; SUS304Ф2	.0mm
SBI-7020 660mm 170mm 610mm 1400mm 25 FeФ1.2mm ; Non-FeФ1.8mm; SUS304Ф2	.5mm
SBI-7025 660mm 220mm 610mm 1500mm 25 FeФ1.5mm ; Non-FeФ2.0mm; SUS304Ф3	.0mm
SBI-7030 660mm 270mm 610mm 1600mm 25 FeФ2.0mm ; Non-FeФ2.38mm; SUS304Ф	3.5mm
SBI-7040 660mm 370mm 610mm 1900mm 18 FeФ2.5mm ; Non-FeФ3.0mm; SUS304Ф4	.0mm
SBI-8010 760mm 70mm 710mm 1400mm 25 FeΦ1.0mm ; Non-FeΦ1.5mm; SUS304Φ2	.0mm
SBI-8015 760mm 120mm 710mm 1400mm 25 FeФ1.2mm ; Non-FeФ1.8mm; SUS304Ф2	.5mm
SBI-8020 760mm 170mm 710mm 1400mm 25 FeΦ1.5mm ; Non-FeΦ2.0mm; SUS304Φ3	.0mm
SBI-8025 760mm 220mm 710mm 1500mm 25 FeФ2.0mm ; Non-FeФ2.38mm; SUS304Ф	3.5mm
SBI-8030 760mm 270mm 710mm 1600mm 25 FeФ2.0mm ; Non-FeФ2.6mm; SUS304Ф4	.0mm
SBI-8040 760mm 370mm 710mm 1900mm 18 FeФ2.5mm ; Non-FeФ3.0mm; SUS304Ф4	.5mm

Remark: Accept tailor-made based on user's products







Product E-Catalogue

Product pictures for reference







Product E-Catalogue









Product E-Catalogue

Freefall Metal Detector specification							
Model No.	Pipe Size	Max. Flow	Dimension	Sensitivity without product's effect			
		Rate		Fe Φ	Non-Fe Φ	SUS304 Φ	
FMD-70	Ф67mm	8000 L/H	470X470X1050mm	0.4mm	0.6mm	0.8mm	
FMD-100	Ф100mm	12000 L/H	470X470X1050mm	0.6mm	0.8mm	1.0mm	
FMD-120	Ф128mm	16000 L/H	470X470X1050mm	0.7mm	1.0mm	1.2mm	
FMD-150	Ф146mm	25000 L/H	470X470X1050mm	0.9mm	1.2mm	1.5mm	
FMD-200	Ф205mm	44000 L/H	470X470X1150mm	1.0mm	1.5mm	2.0mm	
FMD-260	Ф265mm	69000 L/H	560X560X1200mm	1.3mm	1.8mm	2.5mm	
FMD-300	Ф295mm	100000 L/H	560X560X1200mm	1.7mm	2.0mm	3.0mm	
FMD-340	Ф335mm	120000 L/H	560X560X1200mm	2.0mm	2.5mm	3.5mm	

. ...

Company Profile

Shanghai Yuhang Industrial Co., Ltd. was established in Shanghai in 2014. It is a subsidiary of HongKong SINBON Industrial Limited. The factory specializes in the design and production of various filling machine, capping machine, labeling machine, metal detector, check weigher, induction sealing machines, packaging-related equipment etc., also provide solutions for complete packaging production lines. The company has attached great importance to product design and quality control since its establishment. The R&D and design personnel are all senior technical personnel in the industry. More than 10 years of rich practical experience in the industry ensure that our products can well meet the actual needs of users and can also be customized according to the actual needs of users. Users require non-standard customized equipment to meet users' different production equipment needs or solve actual production problems. In addition to making good products, we also actively support users in after-sales service, so that users can buy and use with peace of mind. Although most users are far away in time and space, our technical support is always by your side. The products have patent certificates and CE certificates and our equipment is currently working in most countries.

Contact Us

Shanghai YUHANG Industrial Co., LTD.

Plant Add.: No. 3535 Nanfeng Road, Qingcun Town, Fengxian District, Shanghai, 201414, China Office Add.: RM502, No. 3 Lane 168 Chengnan Rd., Huinan Town, Pudong New District, Shanghai, 201399, China

Tel/Fax: +86-21-20781031/20781032 Email: <u>sales@sinbon.net sales@sinbon.com.hk</u>



